【産業制御系】「産業システムに求められるサイバーセキュリティ対策」

- Moxa Japan 合同会社 出口 博一
 - EBG (Energy Business Group) 担当
- UL サイバーセキュリティ ISA/IEC62443-4 技術者認定

IIoTとインダストリー4.0としてのリスク（サイバーセキュリティの脅威）

セキュリティ インシデントの生産設備への影響

- 工場停止時間
- ノウハウの流出（デザイン、エンジニアリング）
- OT機器へのランサムウェアの侵入
- データの紛失
- 風評被害

ITとOTはサイバーセキュリティの比較

ビジネスの優先事項

機密性

可用性

主な焦点

データの整合性が重要

制御プロセスはダウンタイムを許容できない

保護対象

Windows computers,
servers

Industrial devices: PLC, HMI, meters

環境条件

空調が利いている環境

過酷な環境:
極端な温度、振動、衝撃

2010 年以降、Stuxnet などの ICS ネットワークを標的とした
高度なサイバー攻撃がいくつか発生しています。

Year	Major ICS Security Incidents	Attack Targets
2010	Stuxnet	PLC (Nuclear Power Plant in Iran)
2011	Duqu	Computer/Server (Public Utility in Multiple Countries)
2012	Disttrack/Shamoon	Computer/Server (Oil Company in Saudi Arabia)
2014	Sandworm	SCADA/HMI (Factory Floor in Multiple Countries)
2015	BlackEnergy / Killdisk	HMI/Serial Device (Power Grid in Ukraine)
2016	Industroyer	Circuit Breaker (Power Substation in Ukraine)
2017	Dragonfly	Computer/Server (Public Utility in US/EU)
2018	WannaCry	Computer/Server (Factory Machines in Asia)

OT（ICS）にセキュリティが求められる事になった背景

- イランの各燃焼施設への攻撃（2010年）
 - 関連企業に勤める外部業者が“Stuxnet”に感染したUSBメモリをSCADAに接続
 - StuxnetがPLCを介して、周波数変換装置を操作
 - 結果、8400台の遠心分離機を破壊

The Stuxnet outbreak

A worm in the centrifuge

An unusually sophisticated cyber-weapon is mysterious but important

Sep 30th 2010 | From the print edition

Tim Mann

IT SOUNDS like the plot of an airport thriller or a James Bond film. A crack team of experts, assembled by a shadowy government agency, develops a cyber-weapon designed to shut down a rogue country's nuclear programme. The software uses previously unknown tricks to worm its way into industrial control systems undetected, searching for a particular configuration that matches its target—at which point it wreaks havoc by reprogramming the system, closing valves and shutting down pipelines.

電力以外の業界例（船舶）

- 2023年1月16日、DNV船級協会は、船舶管理・運航プラットフォーム「ShipManager」へのサイバー攻撃を報告
- この攻撃は約1,000隻の船舶に影響を与え、ITサーバーの一時的な停止を引き起こした
- 海運業界を標的とした標的型ランサムウェア攻撃

標的型サイバー攻撃
(重要インフラ)

非標的型、利益目的のサイバー攻撃
(スマート製造)

攻撃手法は標的型から非標的型も (ピンポイント攻撃型から、無差別や利益追求型)

Russian Critical Infrastructure Targeted by Profit-Driven Cybercriminals, DEC 2018

A.P. Moller-Maersk NotPetya; 200M loss, JUN 2017

Saipem Middle East Servers Targeted, DEC 2018

欧州の規制の法制化と規格 (NIS2/CRA/IEC62443)

CRA / NIS2 法規対応の概略図

NIS2指令は2022年12月に《欧州連合官報》で公布され、2023年1月16日に正式に発効した。本指令はEU全体のサイバーセキュリティレジリエンス強化を目的としており、《ネットワークレジリエンス法案（Cyber Resilience Act, CRA）》の政策方針と整合している。各加盟国は指令発効後21か月以内、すなわち2024年10月17日までに、これを国内法規に取り入れなければならない。

CRAは「デジタル要素を有する製品」に対して初めてサイバーセキュリティ要件を定めた世界初の法規であり、指令は運用者（製造者、輸入業者、販売業者を含む）に対して包括的な義務を課している。主な重点は以下の通りである：

製品ライフサイクル責任：経済事業者は製品のライフサイクル全体にわたりサイバーセキュリティ規範を遵守する必要があり、最長で製品の生産終了後10年まで延長される。

ガバナンスおよび技術の二軌道要求：指令はリスクレベルに応じたガバナンスおよび技術的措置の実施を求めており、バランスの取れたサイバーセキュリティ防護を実現する。

サイバーセキュリティリスクレベルに焦点を当てる：すべてのセキュリティ要件は製品に関連するネットワークリスクレベルに基づいて調整され、一律適用されるものではない。

NIS2 / CRA 対応 – IEC 62443 Standards

Security Topics	NIS2	CRA		IEC 62443-4-1	IEC 62443-4-2
Risk Management	✓	✓	●	✓	✓
Incident Response	✓	✓	●	✓	✓
Security Measures	✓	✓	●	✓	✓
Supply Chain Security	✓	✓	●	✓	✓
Secure Product Development	-	✓	●	✓	✓
Technical Security Requirements	-	✓	●	✓	✓
Vulnerability Management	✓	✓	●	✓	✓
Compliance and Certification	✓	✓	●	✓	✓
Network Security and Resilience	✓	-	●	✓	✓
Information Sharing and Cooperation	✓	-		-	-
Monitoring and Logging	✓	-	●	✓	✓
User Awareness and Training	✓	-	●	✓	-
Data Protection and Confidentiality	✓	-	●	-	✓

船舶におけるサイバーセキュリティ規制-IACS UR E26/E27

New IACS Unified Requirements on cyber security support class societies' role to ensure safety

New vessels contracted after 1st of July 2024 will need to be approved wrt cyber security

The requirements come to yards, designers and owners (UR E26) as well as suppliers (UR E27)

Original URs from April 22'. Updated revision 1 of E27 published in Oct 23' while E26 ready by end 23'

Recognizing that cyber incidents on vessels can have a direct and detrimental impact on life, property, and the environment, IACS has already increased its focus on the reliability and functional effectiveness of onboard, subcritical, and critical systems.

IACS identified an early stage test, for ships to be subject against cyber incidents, of sorts of the industry needed to be actively involved, and to recommend a Joint Working Group (JWG) on Cyber Resilience which have already been produced, appropriate existing standards in risk and cyber security, and a practical risk-based approach.

Building on this extensive collaboration, and affording the experience gained from its existing Recommendations, as well as developments in IEC standards, in particular, IEC 62443-3-3/SR 2.6, IACS has adopted two new IACS Unified Requirements (URs) on the cyber resilience of ships.

UR E26 aims to ensure the secure integration of both Operational Technology (OT) and Information Technology (IT) systems into the vessel's network during the design, construction, commissioning and operational life cycle. The UR targets the ship as a collective entity for cyber resilience and covers key aspects: requirement identification, assessment, risk detection, response, and recovery.

UR E27 aims to ensure systems integrity to secure and hardened by third party equipment suppliers. This UR provides requirements for cyber resilience of onboard systems and equipment and provides additional requirements relating to the marine communication and control systems network, as well as product design and development requirements for new devices before their implementation on-board.

NKサイバーセキュリティ関連規則の現状説明

改正内容 鋼船規則X編4章及び5章の適用対象船舶

- 国際航海に従事する旅客船(高速旅客船を含む)
- 総トン数500トン以上の国際航海に従事する貨物船
- 総トン数500トン以上の国際航海に従事する高速船
- 総トン数500トン以上の海洋資源掘削船
- 建設(例えば風力発電設備の保守及び補修, クレーン設備, ドリリングテンダー, 居住等)に従事する自航移動式洋上船

E27 (cont)

4 System Requirements

This section specifies the required security capabilities for CBSs in the scope specified in section 1.3.

Req. No.	Objective	Requirements
11	Limit the use of portable and mobile devices only to those permitted by design.	Limit known value - Fixed value (IEC 62443-3-3/SR 3.6)
12	Information confidentiality	The CBS shall provide the capability to protect the confidentiality of information for which explicit trust authorization is supported, whether at rest or in transit. Note: For wireless networks, cryptographic mechanisms shall be used to protect confidentiality of all information in transit. (IEC 62443-3-3/SR 4.1)
13	Use of cryptography	If cryptography is used, the CBS shall use cryptographic algorithms, key sizes and mechanisms according to: - Limit known value - Fixed value (IEC 62443-3-3/SR 3.6)
16	Resource management	The CBS shall provide the capability to limit the use of resources by security functions to prevent resource exhaustion. (IEC 62443-3-3/SR 7.2)
17	System backup	The identity and location of critical files and the ability to conduct backups of user-level and system-level information (including system state information) shall be supported by the CBS without affecting normal operations. (IEC 62443-3-3/SR 7.3)
18	System recovery and reconstruction	The CBS shall provide the capability to be recovered and reconstituted to a known secure state after a disruption or failure. (IEC 62443-3-3/SR 7.4)
19	Emergency power	The control system shall provide the capability to switch to and from an emergency power supply without affecting the existing security state or a documented degraded mode. (IEC 62443-3-3/SR 7.5)
20	Network and security configuration settings	The CBS traffic shall provide the capability to be configured configurations as determined in guidelines provided by the control system supplier. The CBS shall provide an interface to be able to identify network and security configuration settings. (IEC 62443-3-3/SR 7.6)
21	Least Functionality	The installation, the availability and the access rights of the following shall be limited to the strict needs of the functions provided by the system: - operating system software components, processes and services - network services, ports, protocols, routes and hosts addresses and any software (IEC 62443-3-3/SR 7.7)

30 必要なセキュリティ機能

4.2 Additional security capabilities

The following additional security capabilities are required for CBSs with network communication to untrusted networks (i.e. interface to any networks outside the scope of UR E26).

Table 2

Req. No.	Objective	Requirements
32	Multifactor authentication for human users	Multifactor authentication is required for human users when accessing the CBS from or via an untrusted network. (IEC 62443-3-3/SR 1.1, RE 2)
33	Software process and device identification and authentication	The system shall identify and authenticate software processes and devices (IEC 62443-3-3/SR 1.2)
34	Unsuccessful login attempts	The CBS shall enforce a limit of consecutive invalid login attempts from untrusted networks during a specified time
37	Explicit access request approval	The CBS shall deny access from or via untrusted networks unless explicitly approved by authorized personnel on board. (IEC 62443-3-3/SR 1.13, RE 1)
38	Remote session termination	The CBS shall provide the capability to terminate a remote session either automatically after a configurable time period of inactivity or manually by the user who initiated the session. (IEC 62443-3-3/SR 2.6)
39	Cryptographic integrity protection	The CBS shall employ cryptographic mechanisms to recognize changes to information during communication with or via untrusted networks. (IEC 62443-3-3/SR 3.1, RE 1)
40	Session integrity	The CBS shall protect the integrity of sessions. Invalid session IDs shall be rejected. (IEC 62443-3-3/SR 3.8)
41	Invalidation of session IDs after session termination	The system shall invalidate session IDs upon user logout or other session termination (including browser sessions). (IEC 62443-3-3/SR 3.8, RE 1)

10 追加セキュリティ機能

NKサイバーセキュリティ関連規則の現状説明

改正内容 鋼船規則X編4章及び5章の適用対象システム

- 推進
- 投錨及び係留
- 発電及び分電
- 火災探知及び消火システム
- ビルジ及びバラストシステム、積付計算機
- 水密性及び浸水検知
- 照明 (例えば、非常灯、低位置、航海灯等)
- 安全が要求されるシステムであって、当該システムの混乱又は機能障害が船舶の運航にリスクをもたらすもの (例えば、緊急停止システム、荷役安全システム、圧力容器安全システム及びガス検知システム等)
- 条約により要求される航海設備
- 船級規則又は条約により要求される船内及び船外通信システム
- その他 (自動船位保持設備など)

IEC 62443 Overview

アセットオーナー

システムインテグレーター

製品供給者

ホワイトリストとブラックリストの考え方

アクセスを許された
リスト

ホワイトリスト
Whitelisting

アクセスを拒絶された
リスト

ブラックリスト
Blacklisting

ネットワークソリューション アーキテクチャ

Site Protection

Security Dashboard Console (SDC)

Zone Protection

Industrial Next-Gen Firewall (NGFW)

Cell Protection

Industrial Intrusion Prevention System (IPS)

産業現場のサイバー攻撃・脆弱性例

セキュアバイデザイン

IEC 62443-4-1 認証取得

Ref. Certif. No. FR_Cyber10002
IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE)		
Certificate of Conformity – Industrial Cyber Security Capability		
Type	Process Capability Assessment	
Name and address of the applicant	MOXA Inc. Floor 4, N° 135, Lane 235, Baoqiao Rd., Xindian Dist. New Taipei City Taiwan	
Certificate Coverage (including Version)	Moxa Network Business Group (NBG) Product Secure Development Lifecycle Process	
Standard	IEC 62443-4-1:2018	
Requirements Assessed / Total Requirements	Practice 1 (SM) : 13 / 13 Practice 2 (SR) : 5 / 5 Practice 3 (SD) : 4 / 4 Practice 4 (SI) : 2 / 2 Practice 5 (SVV) : 5 / 5 Practice 6 (DM) : 6 / 6 Practice 7 (SUM) : 5 / 5 Practice 8 (SG) : 7 / 7	
Additional information (if necessary may also be reported on page 2)	☒ Additional information on page 2	
As shown in the Test Report Ref. No. which forms part of this Certificate	164316-744745	
This Certificate of Conformity, issued by the National Certification Body, certifies that the above have been found to be in conformity with the requirements of the Industrial Cyber Security Capability Scheme (IECEE OD-2061) as it relates to the claims declared by the Applicant.
LCIE – Laboratoire Central des Industries Electriques 33, avenue du Général Leclerc – BP8 FR 92 266 Fontenay aux Roses Cedex www.lcie.fr		
Date: 2020/05/20	Julien GAUTHIER Certification Officer	

- Moxaは、2020年5月にIEC 62443-4-1適合証明書を取得し、OTネットワークング企業としていち早く、栄誉を手に入れました。
- IEC 62443-4-1 は、産業オートメーションや制御システムで使用されるセキュアな製品を開発・維持することを目的とし、セキュア開発ライフサイクルを定義しています。
- この証明書は、Moxaが製品開発プロセスにおいて一貫してからセキュアバイデザイン手法を実装していることを確認するものです。また、Moxaが脆弱性を特定し、対応し、顧客と協力してリスクを軽減する能力があることを証明もしています。

セキュリティ機能を内蔵

IEC 62443-4-2認証

デバイスの完全性と真正性

デバイスのファームウェアとブートプロセスの整合性と信頼性を検証する（セキュアブート）

最小化されたデバイス機能

不要なサービスの利用を制限するためのハードニングガイドを提供する。

ユーザー認証と権限付与

各種権限に基づく機器へのログイン時の本人確認

ネットワークアクセス制御と認証

どの機器がネットワークへのアクセスや他の機器との通信を許可されているかを確認する。

コミュニケーション・インテグリティ

設定や管理を行う際の機器への接続を暗号化することが可能

産業ネットワークソリューションの人材・教育に関して

- ネットワーク技術認定制度（社内・社外）

	MXCA	MXCP
Objective	<p>What the Course Provides: This course provides a fundamental understanding of Ethernet technologies and offers hands-on experience in configuring and diagnosing Moxa's Layer 2 switches.</p>	<p>What the Course Provides: This course provides in-depth knowledge of Ethernet switch and router advanced functions, hands-on device configuration, troubleshooting methodologies, and network optimization—ensuring participants gain practical skills they can apply immediately.</p>
Prerequisites	<ul style="list-style-type: none"> • Introduction to OT Cybersecurity <ul style="list-style-type: none"> ▪ Cybersecurity Basics ▪ OT Cybersecurity ▪ IEC 62443 • IEC 62443-4-2 Features <ul style="list-style-type: none"> ▪ NMS with Security Features ▪ IEC 62443-4-2 Features ▪ Login Authentication • Network Security <ul style="list-style-type: none"> ▪ Static Port Lock ▪ MAC Sticky ▪ IEEE 802.1X ▪ MAB 	<ul style="list-style-type: none"> • Perimeter Security <ul style="list-style-type: none"> ▪ L2/L3 Firewall ▪ Deep Packet Inspection ▪ Intrusion Prevention ▪ Centralized Management ▪ VPN • Solution Overview <ul style="list-style-type: none"> ▪ Vendor Security ▪ Product Portfolio
Training Agenda